


ProHD

Model: DT-X92F

9" Full HD Broadcast LCD Monitor



User Manual

Ver: B

Please read this User Manual
throughout before using.

Preface

1. All internal technologies of this product are protected, including device, software and trademark. Reproduction in whole or in part without written permission is prohibited.
2. All brands and trademarks are protected and other relative trademarks in this user manual are the property of their respective owners.
3. Due to constant effort of product development, SWIT Electronics reserves the right to make changes and improvements to the product described in this manual without prior notice.
4. The warranty period of this product is 2 years, and does not cover the following:
 - (1) Physical damage to the surface of the products, including scratches, cracks or other damage to the LCD screen or other externally exposed parts;
 - (2) The LCD dot defects are not over three;
 - (3) Any damage caused by using third-party power adaptors;
 - (4) Any damage or breakdown caused by use, maintenance or storage not according to the user manual.
 - (5) The product is disassembled by anyone other than an authorized service center.
 - (6) Any damage or breakdown not caused by the product design, workmanship, or manufacturing quality, etc.

Maintenance

Warning

1. In order to reduce the risk of fire and electrical shock, do not lay this product in rain or damp places.
2. Please keep away from the strong magnetic field; it may cause the noise of the video and audio signals.

The power

1. Please use the power adapter provided or recommended by the manufacturer in order to avoid damage.
2. For a third party power adapter, please make sure the voltage range, supplied power, and polarity of power lead are fit.
3. Please disconnect the power cable under the following situations:
 - (A). If you do not operate this monitor for a period of time;
 - (B). If the power cable or power adaptor is damaged;
 - (C). If the monitor housing is broken.

The monitor

1. Please don't touch the screen with your fingers, which would probably deface the screen.
2. Please don't press the screen; the LCD is extremely exquisite and flimsy.
3. Please don't lay this product on unstable place.

Cleaning

1. Please clean the screen with dry and downy cloth or special LCD cleanser.
2. Please do not press hard when cleaning the screen.
3. Please do not use water or other chemical cleanser to clean the screen. The chemical may damage the LCD.

Contents

Preface.....	2
Maintenance	3
Contents.....	4
Packing list.....	4
Operation Instructions	5
·Front Panel	5
·OSD	6
·Back Panel	8
Main Menu	9
Sub-Menu	10
Specification	16
Dimensions	17
Trouble-shooting.....	18

Packing list

Basic Package includes:


- 1 X Sun hood
- 1 X Cold shoe / Screw arm trestle
- 1 X SSL-JVC50 battery plate (Interchangeable)
- 1 X V-mount battery plate (Pre-install)
- 1 X Power adaptor

Professional Package includes additional:

- 1 X D-tap to 4-pin XLR cable
- 1 X U shape desktop bracket
- 1 X DV battery
- 1 X HDMI cable (60 cm)
- 1 X Carrying case


Operation Instructions

·Front Panel



(1) Speaker: For SDI/HDMI embedded audio and analog audio monitoring.
(Will not work if headphone socket is plugged in)

(2) Buttons




SOURCE: Press “SOURCE” to select SDI1, SDI2, HDMI, and CVBS signal input

F1~F5: User definable function keys. Please see details in “4. Function key” under “Main Menu”.

WFM: Waveform shortcut key, press “WFM” to quickly turn on or turn off the waveform. Please setup parameters of waveform under “WFM” submenu.

DISPLAY: Press “DISPLAY” to turn on/off the signal status information, audio and video scopes.

(3) Rotary Knob



MENU/ENTER: When the menu is inactivated, presses “MENU/ENTE” to turn on the main menu;
Revolve “MENU/ENTER” to adjust settings or parameters, and press to apply;
When the menu is inactivated, revolve “MENU/ENTER” to adjust sound volume.

BRIGHT: 0-100 value adjustment and the default value is 50


CONTRAST: 0-100 value adjustment and the default value is 50

SATURATION: 0-100 value adjustment and the default value is 50

(4) POWER: Power on/off

(5) TALLY Light: Red, Green and Yellow 3-color TALLY indicator

·OSD



(1) Timecode (SDI)

Under SDI input, it can display Timecode. If no Timecode information is detected, it will be displayed as "TC: UNLOCKED".

User can set function keys F1~F5 or GPI pins as "Timecode" to turn on or off this function.

(2) UMD

Set up the UMD under 'UMD' submenu.

(3) AFD (SDI)

User can set function keys F1~F5 or GPI pins as "AFD" to turn on or off this function. If no relevant information is detected, it will be displayed as "AFD: UNLOCKED".

(4) Audio

Monitor the audio information. The relevant parameters like position, audio channels and blending, etc can be changed under "Audio" submenu.

User can set function Keys F1~F5 or GPI pins as "Audio" to turn on or off this function.

(5) Histogram

User can set function Keys F1~F5 or GPI pins as "Histogram" to turn on or off this function.

(6) Vector

The relevant parameters like Vector position, Vector color and Vector blending, etc. can be changed under "Vector" submenu.

User can set function Keys F1~F5 or GPI pins as "Vector" to turn on or off this function.

(7) Waveform

Press "WFM" on the front panel to turn on/of this function. The relevant parameters like WFM position, WFM color and WFM blending, etc can be changed under "Waveform" submenu.

Introduction of audio and video functions

- ◆ **16-ch embedded audio meters**
Under 2K/3G/HD SDI, it displays 16 channels embedded audio meters. Under SD-SDI and HDMI, it displays 8 channels embedded audio meters. The audio meter is green, and will turn yellow when audio exceeds -20dB, and turn red when audio exceeds -9dB.
- ◆ **Audio alarm**
If the embedded audio value is too low or no embedded audio, it will display “MUTE” or “UNLOCKED” in the audio bar.
- ◆ **Timecode (SDI)**
Under SDI input, it can display the SMPTE timecode (VITC1, VITC2 or LTC) on the top of the screen. If no Timecode information is detected, it will be displayed as “UNLOCKED”.
- ◆ **Waveform (Y, Cb, Cr, R, G, B and single line)**
Under SDI and HDMI input, Y, Cb, Cr, R, G, B and single line waveforms can be selected to display
- ◆ **Vector**
The displayed vector scope pattern is available under both SDI and HDMI, represents saturation as distance from the center of the circle, and hue as the angle, in standard position, around it.
- ◆ **Histogram (R, G, B)**
The histogram is a bar graph that shows the distribution of luminance values in the picture. There're R, G, B histograms that individually displayed simultaneously, available under both SDI and HDMI.
- ◆ **Internal Color Bar**
Under SDI and HDMI input, it has 100% internal color bar which helps to analyze the monitor color and adjust the display parameter.
- ◆ **Peaking focus assist (red/blue switch)**
The Peaking focus assist function is to mark the sharpest edges of the image with red or blue color under SDI and HDMI input, for users to check if the subjects are focused.
- ◆ **Zebra stripes**
Zebra Stripes are used to check if the image is over exposed or not by showing black and white lines on the monitor. It is considered over exposed when luminance value exceeds 90%.
- ◆ **Freeze Frame**
The freeze frame is to capture and display the current broadcast frame.
- ◆ **R/G/B/Mono**
R/G/B/Mono is to display only the blue/red/green primary signal or the luminance signal only so as to monitor the image noise.
- ◆ **False Color**
The false color is used to aid in the setting of camera exposure. Under false color mode, there's a color chart on the bottom of screen for reference. The color from the dark to the bright will be displayed as blue, cyan, green, yellow, orange and red in a consecutive way.
- ◆ **AFD (SDI)**
It is the abbreviation of active format description. AFD is to display the SDI embedded AFD information graphically on the screen.
- ◆ **H/V Delay (SDI)**
Under SDI input, H/V Delay can be used to display line/field blanking signal, and to observe the horizontal and vertical synchronous signal.
- ◆ **UMD**
When using external control unit, it can display the video source ID and tally information on the screen.
- ◆ **Flip and Rotate**
The image can be set up/down flip, or left/right mirror display, like:




Normal

Left to right


Up to down

180° Rotate

·Back Panel



- (1) TALLY Light: Red, Green and Yellow 3-color TALLY indicator.
- (2) DC IN: Connect with 4-pin XLR power adapter, support 6.5V-24V voltage input (Pin 1: Negative, Pin 4: Positive)
- (3) Battery mount connector
The monitor has V-mount plate pre-installed, and supplied an SSL-JVC50 battery plate in package for exchange.
- (4) Audio Socket
AUDIO IN: 3.5mm analog audio input
AUDIO OUT: 3.5mm audio output, SDI/HDMI embedded audio and analog audio output
- (5) Multi-function Socket
GPI: TSL UMD & GPI control socket
USB: User firmware upgrade socket
- (6) Video Signal Interface



- SDI-IN1: SDI input (BNC)
- SDI-LOOP1: SDI loop through output from SDI-IN1 (BNC)
- SDI-IN2: SDI input (BNC)
- SDI-LOOP2: SDI loop through output from SDI-IN2 (BNC)
- CVBS-IN: CVBS input (BNC)
- CVBS-OUT: CVBS loop through output from CVBS-IN (BNC)
- HDMI-IN: HDMI input (HDMI-A)
- HDMI-OUT: HDMI loop through output from HDMI-IN (HDMI-A)

Main Menu

DT-X92F has OSD to adjust the parameters and settings, for example: Picture, color temp., function keys, etc.

1. Press “MENU/ENTER” button, the main menu will pop-up from the left top of the screen. The selected main menu highlights in yellow.

Main Menu		Status
Exit&Status	>	HDMI XXX
Picture	>	User Profile XX
Color Temp	>	Color Temp XXXX
Function Key	>	Scan Mode XXX
GPI	>	Freeze Frame XXX
UMD	>	F1 XXX
Marker	>	F2 XXX
Audio	>	F3 XXX
Vector	>	F4 XXX
Waveform	>	F5 XXX
Display	>	System Version XXX
System	>	
OSD	>	
Key Inhibit	>	

2. Revolve “MENU/ENTER” to select submenu, the selected submenu highlights in yellow, press “MENU/ENTER” to apply and enter into the selected submenu’s items.

3. Revolve “MENU/ENTER” to select the item which needed to adjust, press “MENU/ENTER”, the selected item and its parameters will be highlighted in yellow.

Main Menu		XXXX
Exit&Status	>	Exit
Picture	>	Marker XX
Color Temp	>	Marker Select 15.9
Function Key	>	Safety Area XXX
GPI	>	Fit Marker XXX
UMD	>	Center Marker XXX
Marker	>	Marker Color XXX
Audio	>	Marker Outside XXX
Vector	>	
Waveform	>	
Display	>	
System	>	
OSD	>	
Key Inhibit	>	

4. Revolve “MENU/ENTER” to change the selected item’s parameter, press “MENU/ENTER” to apply and save the settings.

5. Revolve “MENU/ENTER” to select “Exit”, press “MENU/ENTER” to quit submenu. Select “Exit & Status” under the Main Menu and press to quit Main Menu.

Notice:

* The items in gray cannot be set up.

* If there is no operation under the set time, the menu will automatically save settings and quit.

* If the key inhibit function is turned on, except key inhibit function, all other items are in grey. Please turn off the key inhibit function to adjust the items.

Sub-Menu (the default values are marked with underline)

1. Exit & Status

Displays the current status, the details are as down below:

Exit&Status	HDMI* ¹	1080p@50Hz
	User Profile	Default
	Color Temp	6500K
	Scan Mode	Normal
	Freeze Frame	Off
	F1* ²	Audio Bar
	F2	Vector
	F3	Zebra
	F4	Mute
	F5	Marker
System Version	VXXX-XX	

*1 Display the current video signal and format

*2 Display the current function keys setup

2. Picture

To adjust picture parameters

Picture	Exit	
	Contrast	0-100, <u>50</u>
	Brightness	0-100, <u>50</u>
	Saturation	0-100, <u>50</u>
	Sharpness	0-100, <u>50</u>
	Hue	0-100, <u>50</u>
	Backlight	0-100, <u>50</u>

3. Color Temp


To select different color temperature or setup user-defined color parameters.

Color Temp	Exit	
	Gamma	2.2、 <u>2.4</u> 、2.6
	Color Temp	<u>6500K</u> 、5600K、9300K、User
	Red Gain	0-255, 128
	Green Gain	0-255, 128
	Blue Gain	0-255, 128
	Red Bias	0-255, 128
	Green Bias	0-255, 128
	Blue Bias	0-255, 128

* Only "Color Temp" is set to "User", the Red/Blue/Green Gain or Red/Blue/Green Bias can be adjusted.

4. Function key

To define the F1~F5 function keys.




*1 Function keys F1~F5 can be set as the down below functions:

Audio Bar, Histogram, False Color, AFD, H/V Delay, R/G/B/Mono, Marker, Color Bar, UMD, Audio Alarm, Focus Assist, Aspect Ratio, Scan Mode, Zoom Mode, Mute, Freeze Frame, Flip Mode, CVBS, HDMI, SDI1, SDI2, Color Temp, Time Code, Zebra, Vector.

5. GPI


User can set GPI pins to relevant functions to turn on or off this function.



*1 When "GPI control" is set to "On", the monitor can be operated through external GPI control unit.

*2 The GPI pins can be set to the down below functions:

Red Tally, Green Tally, Yellow Tally, Aspect Ratio, Scan Mode, Zoom Mode, Mute, Freeze Frame, Flip Mode, Color Temp, Time Code, Zebra, Vector, Audio Bar, Histogram, False Color, AFD, H/V Delay, R/G/B/Mono, Marker, Color Bar, UMD, Audio Alarm, Focus Assist.



Pin	1	2	3	4
GPI	GPI_1	GPI_2	RXD+	GPI_3
Pin	5	6	7	8
GPI	GPI_4	RXD-	NC	GND

When connecting the GPI pin with ground, the setted function will be turned on, and goes out when disconnecting.

Example 1: Under "GPI" submenu, set "GPI control" to "On", set "2 Pin" to "Red Tally", when the pin 2 of the external GPI control unit is connected with ground, the Tally light on the front panel will turn red. When disconnected, the tally light will turn off.

Example 2: Under "GPI" submenu, set "GPI control" to "On", set "6 Pin" to "Scan Mode", when the pin 6 of the external GPI control unit is connected with ground, the Scan mode will change and follow the sequence: "Normal" → "Overscan" → "Native".

6. UMD

Support "TSL UMD Protocol-V4.0" provided by Television System LTD

UMD	Exit	
	RS485 Address	<u>1</u> -126
	Position	<u>Top</u> , Bottom
	Display Type	<u>Source ID</u> , UMD
	Baud Rate	<u>38400</u> , 9600, 19200
	Parity	<u>Even</u> , None
	Serial Port	<u>RS485</u> , RS232
	Source ID	<u>CAMERA 1</u>

Source ID Setup:

Select "Source ID", revolve "MENU/ENTER" to select the letters and press "MENU/ENTER" to input. Max 8 letters are supported. Select "Exit" to quit and save settings, the source ID will be displayed on top or bottom of the screen.


UMD setup:

- (1) Connect the external control equipment;
- (2) Set "Display Type" to "UMD";
- (3) Set "address", "Baud Rate" and "Parity"
- (4) Adjust the external control equipment and send UMD command, the monitor will display as:

User can set the character and color of the UMD and

the color of Tally1 and Tally2.

Please see "5. GPI" to check the "RS485 pin sequence and definition:




7. Marker

Marker	Exit	
	Marker	<u>Off</u> , On
	Marker Select	Off, 4:3, 13:9, 14:9, 15:9, 16:9, <u>1.85:1</u> , 2.35:1
	Safety Area	Off, 80%, 85%, <u>90%</u> , 93%, 95%
	Fit Marker*1	<u>Off</u> , On
	Center Marker	Off, <u>On</u>
	Marker Color	<u>White</u> , Red, Green, Blue, Black, Gray
	Marker Outside	Off, <u>Gray</u> , Black

*1 When "Fit Marker" is "Off", the size of safety area is benchmarked against the actual display screen, accounting for 80% ~ 95% of actual display screen. When "Fit Marker" is "On", the size of safety area is benchmarked against the area inside the scales marker, accounting for 80% ~ 95% of the area inside the scales marker.

Example:



8. Audio

Audio	Exit	
	Audio Bar	Off、On
	Bar Frame *1	Off、On
	Bar Position	Top Right、Bottom Left、Bottom Right、Top Left
	Bar Blending	Low、Off、High
	Audio Alarm*2	Off、On
	Select Channel*3	Channel 1-2、1-8、1-16
	Left Channel *4	CH1-CH16, <u>CH1</u>
	Right Channel	CH1-CH16, <u>CH2</u>

*1 When “Bar Frame” is set to “Off”, only the audio meter will be displayed. When “Bar Frame” is set to “On”, frame and real-time audio value will be displayed.

*2 When “Audio Alarm” is set to “On”, if no embedded audio is detected, the audio bar will display “UNLOCKED”. If the audio value is too low, the audio bar will display “MUTE”.

*3 Select Channel

Under analog signal, only channel1-2 can be displayed.

Under HDMI signal, channel1-2 and 1-8 can be selected.

Under SDI signal, channel 1-2, 1-8 and 1-16 can be selected.


*4 Audio channels can be selected to output according to the requirements.

When the current “Select Channel” is set to “Channel1-2”, the left channel and right channel output can be selected from Channel1 or channel2.

When the current “Select Channel” is set to “Channel1-8”, the left channel and right channel output can be selected from Channel1 to channel8.

When the current “Select Channel” is set to “Channel1-16”, the left channel and right channel output can be selected from Channel1 to channel 16.

In audio bar, the left channel information will be in green, and the right channel information will be in red.



CH 1~2

CH 1~8

CH 1~16

9. Vector


Vector	Exit	
	Vector	<u>Off</u> , On
	Vector Position	<u>Bottom Right</u> , Center, Top Left, Top Right, Bottom Left
	Vector Blending	Off, <u>Low</u> , High
	Vector Color	Color, White, Green, <u>False Color</u>
	Histogram	<u>Off</u> , On
	Histogram Blending	<u>Low</u> , Off, High

10. Waveform


Waveform	Exit	
	Waveform	<u>Off</u> , On
	WFM Type	<u>Y</u> , Cb, Cr, R, G, B
	WFM Position	<u>Bottom Left</u> , Bottom Right, Center, Top Left, Top Right
	WFM Blending	<u>Low</u> , High, Off
	WFM Color	<u>White</u> , Green, False Color
	WFM Single Line	<u>Off</u> , On
	WFM Line Count *1	0-1079, <u>0</u>

*1: Only the "WFM Single Line" is set to "ON", the "WFM Line Count" can be adjusted.

"WFM Single Line" is to display the selected line waveform of "WFM Line Count"



WFM Single Line: Off



WFM Single Line: On

11. Display

Display	Exit	
	Waveform	<u>Off</u> , On
	Audio Bar	<u>Off</u> , On
	Vector	<u>Off</u> , On
	Zebra	<u>Off</u> , On
	Focus Assist	<u>Off</u> , Blue, Red
	Time Code	<u>Off</u> , On
	Histogram	<u>Off</u> , On
	False Color	<u>Off</u> , On
	AFD	<u>Off</u> , On
	H/V Delay	<u>Off</u> , On
	R/G/B/Mono	<u>Off</u> , Blue Only, Red Only, Green Only, Mono
	Color Bar	<u>Off</u> , On
	Marker	<u>Off</u> , On
	UMD	Off, <u>On</u>

12. System

System	Exit	
	Aspect Ratio	<u>16:9</u> 、4:3
	Scan Mode	<u>Normal</u> 、OverScan、Native
	Zoom Mode	<u>Off</u> 、Zoom1、Zoom2
	Freeze Frame	<u>Off</u> 、On
	Recall Profile	<u>Default</u> 、User1、User2、User3
	Save Profile	<u>User1</u> 、User2、User3
	Source Scan *1	<u>On</u> 、Off
	Logo *2	<u>On</u> 、Off
	Green Mode	<u>Off</u>
	Idle Duration	<u>Off</u>
	Update Driver *3	<u>No</u> 、Yse
	Update Kernel *4	<u>No</u> 、Yes

*1 Source Scan

When set to “Yes”, after turn on the monitor, the signal will be inspected and follow the sequence of “SDI1→SDI2→HDMI→CVBS”.

*2 Logo

When powered on, the screen will display ProHD logo.


*3、*4 Update Driver/ Kernel

Download latest firmware files in USB disk - root directory. Switch on the monitor, and insert USB disk into the USB socket on rear panel.

Enter Menu – System – Update Driver, select YES and the monitor will upgrade automatically, and will restart when upgrade finished.

Enter Menu – System – Update Kernel, select YES and the monitor will upgrade automatically, and will restart when upgrade finished.

Please DO NOT cut off power during firmware upgrade.



13. OSD

OSD	Exit	
	OSD Language	<u>English</u> 、Chinese
	OSD Blending	<u>Low</u> 、Medium、High、Off
	OSD Duration	<u>10Sec</u> 、15Sec、30Sec、60Sec
	OSD Zoom	Off、 <u>On</u>
	Key Led Brightness	<u>Low</u>
	Tally-R Brightness	<u>High</u> 、Low、Medium
	Tally-G Brightness	<u>High</u> 、Low、Medium

14. Key Inhibit

Key Inhibit	Exit	
	Key Inhibit	<u>Off</u> 、On


If the “Key Inhibit” is “On”, there is no response when all the buttons expert ” MENU/ENTER” are pressed, the sreen will be displayed as ” Key Inhibit”.

Specification

LCD Performance		
Size	9 inches	
Display area	191.5×119.7 mm	
Resolution	1920×1200	
Color	8 bit	
Aspect ratio	16:9 / 4:3	
Brightness	450 cd/m ²	
Contrast	1000:1	
Viewing Angle	Horizontal: 170° Vertical: 170°	
Input/output		
Input	BNC×2	2K/3G/HD/SD-SDI ×2
	BNC×1	CVBS input
	HDMI×1	HDMI input
	GPI×1	UMD, GPI control input
	USB×1	For firmware upgarde
	3.5mm×1	analog audio input
Output	BNC×2	2K/3G/HD/SD-SDI loop through output ×2
	BNC×1	CVBS loop through output
	HDMI×1	HDMI loop through output
	3.5mm×1	SDI/HDMI/analog audio output
Video Format		
CVBS	NTSC / PAL	
HDMI	480i / 576i / 480p / 576p	
	1080i (60 / 59.94 / 50)	
	720p (60 / 59.94 / 50)	
	1080p (60 / 59.94 / 50 / 30 / 29.97 / 25 / 24 / 23.98)	
	1080psf (30 / 29.97 / 25 / 24 / 23.98)	
SDI	SMPTE-2048-2	2048×1080p (23.98 / 24 / 25 / 29.97 / 30 / 50 / 59.94 / 60)
		2048×1080i (50 / 59.94 / 60)
	SMPTE-425M-A/B	1080p (60 / 59.94 / 50)
	SMPTE-274M	1080i (60 / 59.94 / 50)
		1080p (30 / 29.97 / 25 / 24 / 23.98)
	SMPTE-RP211	1080psf (30 / 29.97 / 25 / 24 / 23.98)
	SMPTE-296M	720p (60 / 59.94 / 50)
SMPTE-125M	480i (59.94)	
ITU-R BT.656	576i (50)	
General		
Input voltage	DC 6.5V-24V	
Power consumption	18W	
Working temperature	0°C~+40°C	
Working humidity	10%~90%	
Storage temperature	- 15°C~ + 60°C	
Storage humidity	10%~90%	
Dimensions	241×178×50mm	
Net weight (main body)	960g	

Dimensions

The main body (in mm)



Trouble-shooting

Symptom	Possible Causes	Solution
No display	The power is not turned on	Please check if the power is connected, and then press "POWER" button to turn on the monitor
	Unstable power voltage	Reconnect to power supply
	BNC or HDMI cable loose contact or not correctly connected	Check and correctly connect the BNC or HDMI cable
	The attached battery is no power	Change battery
	Using DIY power supply but the polarity is reversed	Refer to the provided power supply, reconnect the power.
Image or color abnormal	Bad contact of BNC or HDMI cable	Change cable
	Video signal has Interference	Remove the interference source(s)
	Improper adjustment of the color parameters	Adjust the "Recall profile" to "Default" under "System" submenu
	Distortion of the image	Reset the Aspect ratio
	Set to Red/Green/Blue only or Mono	Turn the Blue only/ Red Only/ Green Only/Mono off under R/G/B/Mono submenu
	Turn on the "Focus Assist" function	Turn off the "Focus Assist" function
	Turn on the "False Color" function	Turn off the "False Color" function
No audio output	Set to Mute	Turn off MUTE or revolve "MENU/ENTER" to adjust the volume
	Bad contact of signal cable	Change signal cable
	Wrong connection or bad contact of Audio cable	Connect to the correct input socket.

ProHD

This model is manufactured by **SWIT Electronics Co., Ltd.**

and distributed, warranted and supported in Europe by **JVCKENWOOD Deutschland GmbH**

To obtain service or for further information, please contact:

JVCKENWOOD Deutschland GmbH · Konrad-Adenauer-Allee 1-11 · 61118 Bad Vilbel

Telefon: +49 (0) 6101 / 4988 - 0 · Telefax: +49 (0) 6101 / 4988 - 50

www.jvcpro.eu