



GY-HC500EN GY-HC550EN GY-HC550ESBN





Photo shows GY-HC500 with optional microphone.









MPEG-2 💒 💥





NDI® | HX Capability for GY-HC500 Series Camcorders

The NDI®|HX mode modification adds the capability for the GY-HC500, GY-HC550, and GY-HC550ESBN to become a live video source for NDI®|HX compatible hardware or software connected to the local area network (LAN).

Features available in the NDI®|HX mode include automatic camera discovery on the LAN by supported hardware and software, tally support, and IP remote control capability.

NDI®|**HX Mode Selection**

The NDI® HX live video source capability is a mode of operation in addition to the camcorder's existing output formats. The modification adds the NDI®|HX mode to the Recording Format System selection of the camcorder. Selecting NDI®|HX sets the camera to operate solely as a live video source.



Modification for Current GY-HC500 Series

Current owners of the GY-HC500, GY-HC550, and GY-HC550ESBN will be able to have their camcorders modified to incorporate the new NDI® HX features through JVC. Please contact JVCKENWOOD Europe.

■System



■NDI® | HX Streaming mode

1920x1080, 1280x720 Resolution Bit Rate 1920x1080: 20M/16M/12M 1280x720: 16M/12M/8M Frame Rate 60p, 50p Recording Not Available

Accessories



NDI®|HX is a registered trademark of Vizrt Group.

Product and company names mentioned here are trademarks or registered trademarks of their respective owners

HDMI, the HDMI logo and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC.

OR Code is a registered trademark of Denso Wave Incorporated.

Simulated pictures.Values for weight and dimensions are approximate. E.&O.E. Design and specifications subject to change without notice. Copyright © 2023, JVCKENWOOD Corporation. All Rights Reserved.

DISTRIBUTED BY

For Instruction Manual



http://www32.jvckenwood.com/ jvc/manual_e/index.asp

JVC Professional Video website



pro.jvc.com



eu.ivc.com/pro